

## PRODUCT CATALOG – DUPLEX SERVICE DROP

Code Name	Phase	Conductor size AWG or MCM	Insul. Thick, (mils)	Bare Neutral Messenger Size A WG or MCM*	Rated Strength (Lbs)	Lbs/1000 Ft. Cross linked Polyeth	Polyeth
<b>With 6201 Alloy Neutral Messenger</b>							
<b>Chihuahua</b>	6	Solid	45	6	7/w	1,110	65.8
<b>Vizsla</b>	6	7/w	45	6	7/w	1,110	67.2
<b>Harrier</b>	4	solid	45	4	7/w	1,760	99.9
<b>Whippet</b>	4	7/w	45	4	7/w	1,760	101.9
<b>Schnauzer</b>	2	7/w	45	2	7/w	2,800	156.2
<b>Heeler</b>	1/0	19/w	60	1/0	7/w	4,460	250.8
<b>With AAC Neutral Messenger</b>							
<b>Pekingese</b>	6	Solid	45	6	7/w	563	61.7
<b>Collie</b>	6	7/w	45	6	7/w	563	63.1
<b>Dachshund</b>	4	Solid	45	4	7/w	881	93.4
<b>Spaniel</b>	4	7/w	45	4	7/w	881	95.4
<b>Doberman</b>	2	7/w	45	2	7/w	1,350	145.7
<b>Malmute</b>	1/0	19/w	45	1/0	7/w	1,990	234.2
<b>With ACSR Neutral Messenger</b>							
<b>Setter</b>	6	Solid	45	6	6/1	1,190	73.2
<b>Shepherd</b>	6	7/w	45	6	6/1	1,190	74.6
<b>Eskimo</b>	4	Solid	45	4	6/1	1,860	111.6
<b>Terrier</b>	4	7/w	45	4	6/1	1,860	113.6
<b>Chow</b>	2	7/w	45	2	6/1	2,850	174.7
<b>Bull</b>	1/0	19/w	60	1/0	6/1	4,380	280.3

\* Designated sizes are ACSR 611 diameter equivalent and AAC with equivalent resistivity per ASTM B-399 for 6201.

The code words as given apply to conventional Polyethylene line wire. For cross-linked polyethylene, the suffix XLP should be added such as "Hombeam -XLP"

Standards: ASTM B-230, B-231, B-232 and B-399, ICEA S-61-402 and S-66-524. REA Approved.

Packaging: Available in 500 ft. coils for sizes 2 A ING and smaller and in long lengths on reels.

The above data are approximate and subject to normal manufacturing tolerances.