

## PRODUCT CATALOG – TRIPLEX SERVICE DROP

Code Name	Phase Conductors		Insul. Thick. (mils)	Bare	Neutral	Rated Strength (Lbs)	Lbs1000 Ft.	
	Size AING or MCM	Size or		Size or	Messenger A WG MCM**		Cross linked Polyeth	Polyeth
<b>With Full Size ACSR Messenger</b>								
<b>Whelk</b>	4	solid	45	4	6/1	1,860	169	165
<b>Periwinkle</b>	4	7/w	45	4	6/1	1,860	176	172
<b>Conch</b>	2	7/w	45	2	6/1	2,850	267	261
<b>Nerrina</b>	1/0	7/w	60	1/0	6/1	4,380	430	419
<b>Cenia</b>	1/0	19/w	60	1/0	6/1	4,380	426	416
<b>Rucina</b>	2/0	7/w	60	2/0	6/1	5,310	530	519
<b>Triton</b>	2/0	19/w	60	2/0	6/1	5,310	526	514
<b>Cherrystone</b>	3/0	7/w	60	3/0	6/1	6,620	656	643
<b>Mursia</b>	3/0	19/w	60	3/0	6/1	6,620	650	638
<b>Razor</b>	4/0	7/w	60	4/0	6/1	8,350	814	799
<b>Zuzara</b>	4/0	19/w	60	4/0	6/1	8,350	805	792
<b>With ACSR Reduced Size Messenger</b>								
<b>Cockle</b>	2	7/w	45	4	6/1	1,860	233	227
<b>Janthina</b>	1/0	7/w	60	2	6/1	2,850	376	365
<b>Ranella</b>	1/0	19/w	60	2	6/1	2,850	372	362
<b>Cavolinia</b>	2/0	7/w	60	1	6/1	3,550	462	451
<b>Clio</b>	2/0	19/w	60	1	6/1	3,550	458	446
<b>Sandollar</b>	3/0	7/w	60	1/0	6/1	4,380	570	557
<b>Aega</b>	3/0	19/w	60	1/0	6/1	4,380	565	552
<b>Cuttlefish</b>	4/0	7/w	60	2/0	6/1	5,310	706	691
<b>Cerapus</b>	4/0	19/w	60	2/0	6/1	5,310	699	684

\*\* Designated sizes are ACSR 611 diameter equivalent and AAC with equivalent resistivity per ASTM B-399 for 6201.

The code names as given apply to conventional polyethylene line wire. For cross-linked polyethylene, the suffix XLP should be added such as 'Hombeam -XLP'

Standards: ASTM B-230, B-231, B-232 and B-399, ICEA S-61-402 and S-66-524. REA Approved, Packaging: Available in 500 ft. coils for sizes 2 A WG and smaller and in long lengths on reels.

The above data are approximate and subject to normal manufacturing tolerances,