

PRODUCT CATALOG – SINGLE CONDUCTOR 600 VOLT SECONDARY UD (Type UD)

Code Name	Cond. Size AWG or MCM		Insul Thickness (mils)	Outside Diameter (inches)	Lbs/1000 Ft.
Princeton	6	7/w	60	.303	47
Mercer	4	7/w	60	.350	67
Clemson	2	7/w	60	.408	97
Kenyon	1	19/w	80	.486	127
Harvard	1/0	19/w	80	.526	153
Yale	2/0	19/w	80	.570	185
Tufts	3/0	19/w	80	.620	224
Beloit	4/0	19/w	80	.676	273
Hofstra	250	37/w	95	.752	330
Gonzaga	300	37/w	95	.805	386
Rutgers	350	37/w	95	.855	441
Emory	500	37/w	95	.983	603
Duke	600	61/w	110	1.090	724
Furman	700	61/w	110	1.159	836
Sewanee	750	61/w	110	1.192	888
Forcham	1000	61 /w	110	1.341	1152

PRODUCT CATALOG – DUPLEX CONDUCTOR 600 VOLT SECONDARY UD (Type UD)

Code Name	Phase Conductors		Neutral		Outside Diameter (inches).	Lbs/11000 Ft
	Size AWG or MCM	Insul. Thick. (mils)	Size AWG or MCM	Insul. Thick (mils)		
Clafin 6	7/w	60	6 7/w	60	.606	104
Delgado 4	7/w	60	4 7/w	60	.700	138