

PRODUCT CATALOG – QUADRUPLEX CONDUCTOR 600 VOLT SECONDARY UD (Type UD)

Code Name	Phase Conductors			Neutral			Outside Diameter (inches)	Lbs. 11000 Ft.
	Size AING or MCM	Insul. Thick. (mils)	Size AING or MCM	Insul. Thick. (mils)	Size AING or MCM	Insul. Thick. (mils)		
Tulsa	4	7/w	60	4	7/w	60	.845	270
Dyke	2	7/w	60	4	7/w	60	.945	361
Wittenberg	2	7/w	60	2	7/w	60	.985	391
Notre Dame	1/0	19/w	80	2	7/w	60	1.231	562
Purdue	1/0	19/w	80	1/0	19/w	80	1.270	619
Syracuse	2/0	19/w	80	1	19/w	80	1.338	688
Lafayette	2/0	19/w	80	2/0	19/w	80	1.376	745
Swarthmore	3/0	19/w	80	1/0	19/w	80	1.449	832
Davidson	3/0	19/w	80	3/0	19/w	80	1.497	903
Wake Forest	4/0	19/w	80	2/0	19/w	80	1.587	1014
Earlham	4/0	19/w	80	4/0	19/w	80	1.632	1103

To determine ampacity by conductor size, please consult the National Electric Code, latest edition.

Standards: ASTM B-230 and B-231, ICEA S-66-524. REA Approved

Packaging: Available in 500 ft. coils (4 and 2 A ING), 500 ft. reels, 1, 000 ft, reels and long lengths.

The above data are approximate and subject to normal manufacturing tolerances.